



US009638389B2

(12) **United States Patent**
Fukui

(10) **Patent No.:** **US 9,638,389 B2**
(45) **Date of Patent:** **May 2, 2017**

(54) **WATERPROOF STRUCTURE FOR VEHICLE LIGHTING DEVICE**

(56) **References Cited**

U.S. PATENT DOCUMENTS

- (71) Applicant: **TOYODA GOSEI CO., LTD.**,
Kiyosu-shi, Aichi-ken (JP)
- (72) Inventor: **Hiroataka Fukui**, Kiyosu (JP)
- (73) Assignee: **TOYODA GOSEI CO., LTD.**,
Aichi-pref. (JP)
- (*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 135 days.

6,594,417	B1 *	7/2003	Hulse	B60Q 3/004
					362/487
2004/0179358	A1 *	9/2004	Tufte	B60Q 1/32
					362/223
2004/0184276	A1 *	9/2004	Moll	B60Q 1/32
					362/487
2005/0254253	A1 *	11/2005	Yeh	B60Q 1/0041
					362/514
2005/0270794	A1 *	12/2005	Okamoto	F21S 48/211
					362/555
2007/0223218	A1 *	9/2007	You	F21S 8/031
					362/231

(Continued)

(21) Appl. No.: **14/633,318**

FOREIGN PATENT DOCUMENTS

(22) Filed: **Feb. 27, 2015**

(65) **Prior Publication Data**

US 2015/0369444 A1 Dec. 24, 2015

(30) **Foreign Application Priority Data**

Jun. 19, 2014 (JP) 2014-126324

- (51) **Int. Cl.**
B60Q 1/18 (2006.01)
F21S 8/10 (2006.01)
F21V 8/00 (2006.01)

- (52) **U.S. Cl.**
CPC **F21S 48/33** (2013.01); **F21S 48/2206**
(2013.01); **F21S 48/2212** (2013.01); **F21S**
48/2237 (2013.01); **F21S 48/2268** (2013.01);
G02B 6/0088 (2013.01)

- (58) **Field of Classification Search**
CPC F21S 48/2237; F21S 48/1241; F21S 48/33;
F21S 48/335
USPC 362/511
See application file for complete search history.

JP	7-30412	U	6/1995
JP	3286162	B2	3/2002

Primary Examiner — Jong-Suk (James) Lee

Assistant Examiner — Eric T Eide

(74) *Attorney, Agent, or Firm* — Posz Law Group, PLC

(57) **ABSTRACT**

A vehicle lighting device includes a case, a lens, a light guide, a waterproof member, hooks, and catches. The catches are elastically deformed outward to separate from an accommodation portion so that the hooks enter the catches from the side closer to the accommodation portion. Engaging surfaces of the hooks engage with catch surfaces of the catches so that the case and the lens are joined. The joining causes the waterproof member to be compressed. The engaging surfaces and the catch surfaces are inclined by an equal angle relative to an imaginary plane perpendicular to the arrangement direction of the case and the lens such that the catch surfaces are located inward of the engaging surfaces and close to the accommodation portion.

3 Claims, 8 Drawing Sheets

